

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 1 of 12

1. Identification of the substance/preparation and of the company/undertaking *

1.1. Information on the product

Trade name:

Majesthetik-Stumpfix

UFI:

M630-W09S-V00K-9DHF

1.2. Relevant identified uses of the substance/preparation and uses that are inadvisable

Relevant identified uses:

technical resin - two-componount die material

1.3. Details about the supplier of the safety data sheet

Manufacturer/Supplier:

Company name:

picodent Dental Produktions- und Vertriebs-GmbH

Street:

Lüdenschneider Str. 24-26

City:

D-51688 Wipperfürth

Telephone:

+49 2267 6580-0

E-Mail:

picodent@picodent.de

Internet:

www.picodent.de

Department for information:

picodent Dental Produktions- und Vertriebs-GmbH

Telephone-No. +49 2267 6580-0

1.4. Emergency contact number:

Medical Emergency information in case of poisoning:

Poison Information Center Mainz

-24 h – Phone: +49 6131 19240

advisory service in German or English language

2. Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Sens. 1; H317

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

urethane dimethacrylate (UDMA)

Acrylic resin

dibenzoyl peroxide

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)

Signal word:

Warning

Pictograms:



Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 2 of 12

Signal word:
UFI:

Danger
F50H-3S3F-H01K-PWRD

Hazard statements

H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P391 Collect spillage.
P501 Dispose of contents/container in accordance with local regulation.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

3. Composition/information on ingredients

3.2. Mixture

Chemical characterization

Mixture of acrylic resins, fillers and initiators.

Relevant ingredients

CAS No	Chemical name	EC No	Index No	REACH No	Quantity
		Classification (Regulation (EC) No 1272/2008)			
72869-86-4	urethane dimethacrylate (UDMA)				35 - 65 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411				
	Acrylic resin				10 - 40 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411				
94-36-0	dibenzoyl peroxide				< 1 %
	202-327-6		617-008-00-0		
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1; H241 H319 H317				
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)				< 1 %
	278-355-8		015-203-00-X		
	Repr. 1B, Skin Sens. 1B, Aquatic Chronic 2; H360Fd H317 H411				

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
72869-86-4		urethane dimethacrylate (UDMA)	35 - 65 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
		Acrylic resin	10 - 40 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
94-36-0	202-327-6	dibenzoyl peroxide	< 1 %
		oral: LD50 = > 5000 mg/kg	
75980-60-8	278-355-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = > 5000 mg/kg	

4. First aid measures

4.1. Description of first aid measures

General Information	Get medical advice/attention if you feel unwell. Immediately remove any contaminated clothing, shoes or stockings.
After inhalation	Get medical advice/attention if you feel unwell. Provide fresh air.
After contact with skin	After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. If skin irritation occurs: Get medical advice/attention.
After contact with eyes	After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.
After ingestion	Do NOT induce vomiting. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media
Unsuitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide.
Full water jet

5.2. Special hazards arising from the substance or mixture:

In case of fire may be liberated: Carbon monoxide, Carbon dioxide, Hazardous decomposition products.

5.3. Advice for firefighters Additional information

In case of fire: Wear self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 4 of 12

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Larger quantities: Take up mechanically (by pumping). Smaller quantities and/or residues: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect from the action of light. Keep only in the original container at a temperature between 4 -25 °C. Can polymerize with intense heat release.

Hints on joint storage

Do not store together with:
Oxidising agent, strong
Food

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 5 of 12

8. Exposure controls/personal protection *

8.1. Control parameters

CAS No	Name of agent	Exposure route	Effect	Value
72869-86-4	urethane dimethacrylate (UDMA)			
Worker DNEL, long-term		dermal	systemic	1,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	3,3 mg/m ³
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)			
Worker DNEL, long-term		dermal	systemic	0,233 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,145 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,0833 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
72869-86-4	urethane dimethacrylate (UDMA)	
Freshwater		0,01 mg/l
Marine water		0,001 mg/l
Freshwater sediment		4,56 mg/kg
Marine sediment		0,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,61 mg/l
Soil		0,91 mg/kg
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)	
Marine water		0,00014 mg/l
Freshwater sediment		0,115 mg/kg
Marine sediment		0,0115 mg/kg
Soil		0,0222 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection

Hand protection

Gloves should be replaced regularly, especially after extended contact with the product. For each work-place a suitable glove type has to be selected.

Skin protection

Wear suitable protective clothing.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	pasty	
Colour:	ivory-coloured	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		flammable liquids
Lower explosion limits:		not determined
Upper explosion limits:		not determined

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 6 of 12

Flash point:	> 100 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Further Information

Product has not been tested. The statement is derived from the properties of the components.

10. Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.
Avoid expressing and application of large quantities (heat of reaction, fire hazard).

10.4. Conditions to avoid

Protect from the action of light. Keep only in the original container at a temperature between 4 -25 °C. Can polymerize with intense heat release.

10.5. Incompatible materials

Oxidising agent, Reducing agent, Heavy metals, Acids Alkali (lye)

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 7 of 12

11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclenes

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Dose	Species	Source	Method
72869-86-4	urethane dimethacrylate (UDMA)				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >2000 mg/kg	Rat	OECD 402	
	inhalation (4 h) dust/mist	LC50 >5 mg/l			
	Acrylic resin				
	oral	LD50 > 2000 mg/kg	Rat	OECD 423	
	dermal	LD50 > 2000 mg/kg	Rat	OECD 402	
94-36-0	dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rat	ECHA	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (urethane dimethacrylate (UDMA); Acrylic resin; dibenzoyl peroxide; Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO))
May cause sensitization by skin contact.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 8 of 12

12. Ecological information

12.1. Toxicity

CAS No	Chemical name	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
72869-86-4	urethane dimethacrylate (UDMA)	Acute fish toxicity	LC50 10,1 mg/l	96 h	Danio rerio (zebrafish)	OECD 203	
		Acute algae toxicity	ErC50 >0,68 mg/l	72 h	Desmodesmus subspicatus	OECD 201	
		Acute crustacea toxicity	EC50 >1,2 mg/l	48 h	Daphnia magna (Big water flea)		
	Acrylic resin	Acute fish toxicity	LC50 1,65 mg/l	96 h	Danio rerio (zebrafish)	OECD 203	
		Acute algae toxicity	ErC50 1,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201	
		Acute crustacea toxicity	EC50 2,36 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)	Acute fish toxicity	LC50 1,4 mg/l	96 h	Cyprinus carpio (Common Carp)	ECHA	OECD 203
		Acute algae toxicity	ErC50 >2,01 mg/l	72 h	Daphnia magna (Big water flea)	ECHA	OECD 201
		Acute crustacea toxicity	EC50 3,53 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
		Acute bacteria toxicity	EC50 >10003 mg/l ()	h	Activated sludge	ECHA	OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No C	hemical name	Method	Value	d	Source
72869-86-4	urethane dimethacrylate (UDMA)	Biodegradation	22 %	28	OECD 301 F
	Acrylic resin	OECD 301 F	27 %	56	
		Not readily biodegradable (according to OECD criteria)			
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)	OECD 301 F	0-10 %	28	
		Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)			

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 9 of 12

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.
Do not allow to enter into surface water or drains.

13. Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Avoid expressing and application of large quantities (heat of reaction, fire hazard). Small quantities can be polymerized by light and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities. Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - used product

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - contaminated packaging

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

14. Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 375 601

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 10 of 12

Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: E

Other applicable information (land transport)

SV 375: These substances, when carried in single or combination packagings of a net quantity not exceeding 5 litres of liquids or a net mass not exceeding 5 kg of solids per single or combination packaging, are not subject to the other provisions of ADR, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:
(ACRYLIC RESIN)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Special Provisions:

274, 335, 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Special Provisions:

A97 A158 A197

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450 L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450 L

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 11 of 12

A 197:

These substances are not subject to other provisions of these Regulations when carried in single or combination packagings with a net quantity per single or inner packaging not exceeding 5 L for liquids and a net weight not exceeding 5kg for substances, provided the packagings meet the general requirements of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Other applicable information (air transport)

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Danger releasing substance:

Yes

ACRYLIC RESIN

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (TPO)
Entry 75

Restrictions on use (REACH, annex XVII):

National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

16. Other information *

Abbreviations and acronyms

Org. Perox

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Repr: Reproductive toxicity

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification

Classification procedure

Skin Sens. 1; H317

Calculation method

Aquatic Chronic 2; H411

Calculation method

Safety Data Sheet

according to regulation (EU) No. 1907/2006

Printing date: 06/03/2026

Majesthetik-Stumpfix

Page 12 of 12

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data compared to the previous version Rev.-No. 2.0 altered.